

## REMOTE LINE PRINTER



### FEATURES

- Printer alarms can be acknowledged at each addressable supervised printer
- Three levels of audio signal identify the alarm, trouble, or restore event
- User can select type of data to print at each of up to eight printers selected
- 32-Line Driver Rack may be used to isolate the data lines for each printer

### SPECIFICATIONS

#### Dimensions

Height: 3.2 in  
Width: 14.2 in.  
Depth: 10.8 in

#### Net Weight

10 lbs.

#### Power

10/220/240 V, 5-/6- Hz

#### Environmental

- Operating Temp.: 5°-40° C
- Storage Temp.: -40-70° C
- Operating Humidity: 5-80% non-condensing
- Storage Humidity: 5-95% non-condensing

### Product Description

The Remote Line Printers acts as system status indicators for the System 3505s. Information displayed at the System 3505 is also printed (selectively) on the remote line printers. Each line printed on a printer represents the complete display of each screen (page) entered in the setup for a specific zone.

The printer can be field selectable to operate with the following protocols: RS-485, RS-232, or Current Loop. The Printer Option must be ordered and installed prior to installing the Remote Line Printer. The RS-485 printer option (P/N 010001-0047) is recommended because it allows expansion to 8 remote line printers. For the Printer Option with RS-232 connection, please use P/N 010001-0045.

This printer is compatible the System 3505.

